



RADIUS
AEON

AG06/1

RESILIENT SEATED GATE VALVE OPTIVALVE™ WITH WELDED ENDS

DN50 - DN300



Patented dual seal technology, the optimal Resilient Seated Gate Valve provides perfect seal tightness with low torque, minimal number of turns, and full traceability.

Application:



Gas & Biogas and Natural gas lines at medium working pressure and temperature range from -20° to +60°C

Design features

- PSteel ends for welding into steel pipe system
- Patented double seated integral ductile iron wedge, fully NBR encapsulated
- Very low closing torque with perfectly smooth patented guiding
- Stem seals fully replaceable under pressure
- Patented primary seal integrated in the wedge to achieve perfect top seal when valve is opened
- The design is approved for use with hydrogen and a mixture of hydrogen and natural gas up to a working pressure 7 bar

Technical Details

Maximum Operating Pressure MOP:

16 bar / PN16
(7 bar for double-block-and-bleed - optional)
7 bar when used with Hydrogen gas

Working temperature:

-20 to +60°C

Construction complies to:

EN 13774 Class 1/2, GIS/V7-1 Class A/B,
TSG D7002-2023

Certification:

CE (PED 2014/68/UE), DVGW, BSI Kitemark, TSG

Coating:

250 µm FBE coating, external and internal

PUR available on request:


Internally - 250 µm FBE coating
Externally - polyurethane (PUR) to EN 10290





AG06/1

No	Part Name	Material
1	Body	Staliwo GS-C25N
2	Bonnet	Ductile Iron EN-GJS-500-7
3	Wedge	D.I., NBR encapsulated EN-GJS-400-18/ EN-GJS-500-7
4	Wedge Nut	Brass
5	Guide Shoe	Plastic POM
6	Stem	Stainless Steel X20Cr13 / 1.4021 / 420
7	Gland Bush	Brass
8	Bonnet Gasket	Elastomer NBR
9	O-ring Seal	Elastomer NBR
10	Dust Seal	Elastomer NBR
11	Bonnet Screws	Stainless Steel A2-70
12	Bottom Washer	Plastic POM
13	Acetal Circlip	Steel Ring
14	Steel Connector	Steel pipe S265JR



- Lifting eye-bolts standard from DN150

Dimension (mm & kg)

DN	50	80	100	150	200	250	300	
AG06/1	EPOXY POWDER COATING							
	PN16	BG0561	BG0861	BG1061	BG1561	BG2061	BG2561	BG3061
	POWDER COATING WITH EPOXY PAINT AND ADDITIONAL LAYER OF POLYURETHANE (PUR) - BLACK							
	PN16	BG0562	BG0862	BG1062	BG1562	BG2062	BG2562	BG3062
L*	570	550	520	530	570	590	620	
H	329	315	349	495	558	648	728	
B	37	50	63	90	120	145	170	
D	57	89	108	159	219	273	325	
E	3,0	4,0	4,0	5,0	6,0	7,0	8,0	
Stem Top Square □S	17	17	19	19	24	27	27	
Turns to open/close	7 ½	7 ½	9 ¼	13 ¾	18	21 ¾	26 ⅓	
Closing Torque [Nm]	50±10	70±10	80±10	100±20	130±20	180±20	200±20	
Weight	15,6	17,1	23,3	39,5	68,5	90,9	138,8	

Notes:

- Clockwise to close