



AW06/1

RESILIENT SEATED GATE VALVE OPTIVALVE PLUS™ FLANGED END F5 PREPARED FOR ACTUATOR

DN80 - DN300 (EPDM)

The Resilient Seated Gate Valve type EcoValve is a highly reliable valve with superior characteristics, in compliance with all international standards.

Application:



Drinking water, municipal sewage cleaned, cooling and other non-aggressive media.

Design features

- Patented double seated integral ductile iron wedge, fully EPDM encapsulated
- Very low closing torque with perfectly smooth patented guiding
- Three stem seals fully replaceable under pressure
- Patented primary seal integrated in the wedge to achieve perfect top seal when valve is opened
- Integrated guide shoes on the Wedge


Technical Details:

Face to Face in accordance to: EN 558-1 Series 15	Construction complies to: EN 1074-1&2, EN 1171
Maximum working pressure PFA: 16 bar / PN16	Flange type: EN 1092-2 PN10 i PN16
Working temperature: Maximum +70°C	Coating: 250 µm FBE coating, external and internal





No	Part Name	Material
1	Body	Ductile Iron EN-GJS-500-7
2	Bonnet	Ductile Iron EN-GJS-500-7
3	Adaptor with Flange	Ductile Iron EN-GJS-500-7
4	Wedge	D.I., EPDM encapsulated EN-GJS-500-7
5	Wedge Nut	Aluminium Bronze
6	Guide Shoe	Plastic POM
7	Stem	Stainless Steel X20Cr13 / 1.4021 / 420
8	Gland Bush	Aluminium Bronze
9	Support Bush	Aluminium Bronze
10	Bonnet Gasket	Elastomer EPDM
11	O-ring Seal	Elastomer EPDM
12	Bonnet Screws	Stainless Steel A2-70
13	Housing Bolts	Stainless Steel A2-70



Dimension (mm & kg)

DN		80	100	125	150	200	250	300
AW06/1	PN10	BW0833	BW1033	BW1273	BW1533	BW2036	BG2536	BG3036
	PN16					BW2033	BG2533	BW3033
L		280	300	325	350	400	450	500
H		304	338	460	448	528	595	676
H1		345	379	500	489	567	637	717
B		95	102	120	134	165	196	225
K PN16 / PN10		160	180	210	240	295	355 / 350	410 / 400
b x n PN16 / PN10		19x8	19x8	19x8	23x8	23x12 / 23x8	27x12 / 23x12	27x12 / 23x12
D		200	220	250	285	340	405	460
d1		125	125	125	125	125	175	175
d2		102	102	102	102	102	140	140
d3		20	20	20	20	20	30	30
d4 x m		11x4	11x4	11x4	11x4	11x4	17,5x4	17,5x4
ISO 5210		F10	F10	F10	F10	F10	F14	F14
Parallel Key		6x6x28	6x6x28	6x6x28	6x6x28	6x6x28	8x7x32	8x7x32
Closing torque [Nm]		50	60	80	80	100	140	150
Turns to open/close		7 ½	9 ¼	13 ¾	13 ¾	18	21 ¾	26 1/3
Kv [m3/h]		654	1252	1805	2818	5601	8751	12602
Weight		23	26,4	45,7	47,9	75,6	101,3	150,7